


Bench





IMPORTANT: Read all instructions carefully before using this product. Retain this owner's manual for future reference.

The specifications of this product may vary from this photo, subject to change without notice.

Owner's Manual Le Manuel Du Proprietaire



PLEASE DO NOT RETURN THIS PRODUCT TO THE STORE.

STOP and contact customer service if you have any questions regarding assembly or proper operation of the machine.

Email us at:

Service@paradigmhw.com

Or call us at:

1-844-641-7920

Hours:

8:00 am to 5:00 pm

Monday Thru Friday

TABLE OF CONTENT

SERVICE	2
LABEL PLACEMENT	3
IMPORTANT SAFETY GUIDELINES	4
OVERVIEW DRAWING	5
PART LIST	6
HARDWARE & TOOLS PACK	7
ASSEMBLY	8
ADJUSTMENTS	13
TRANSPORTATION	17
WARRANTY	18
PARTS REQUEST FORM	19

SERVICE

IMPORTANT: FOR NORTH AMERICA ONLY

For damaged or defective product, questions, replacement parts or any other service support, please contact our customer service department by the below methods:

For The Best Service, please Email:

service@paradigmhw.com

Response Time: 1-2 Business Days

Emailing us with the information above will be the best method to receive a response during peak business hours

Website:

www.paradigmhw.com

Toll-Free:

1-844-641-7920

(8:00 AM - 5:00 PM Pacific Standard Time, Monday Thru Friday)

Response time may vary via calling

Please have the following information ready when requesting for service:


- Your name
- Phone number
- Model number
- Serial number
- Part number
- Proof of Purchase

For damaged or defective product please contact our customer service before returning to the store.

Paradigm Health & Wellness, Inc. 1189 Jellick Ave.

City of Industry, CA 91748, USA

LABEL PLACEMENT



IMPORTANT SAFETY GUIDELINES

Read all instructions carefully before assembling and operating this product. This unit is designed with optimum safety in mind. Retain this owner's manual, do not remove any safety labels from the machine, and keep the original purchase receipt for future reference.

- 1. Make sure your equipment is correctly assembled before you use it.
- 2. Be sure all screws, nuts, and bolts are tightened prior to use.
- 3. Always wear proper exercise apparel when using the equipment. Use care when getting on or off the unit.
- 4. If any time you feel faint, light-headed or dizziness while operating the equipment, stop exercising immediately. You should also stop exercising if you are experiencing pain or any kind of discomfort.
- 5. Keep children and pets away from the equipment at all times.
- 6. Only one person should use the equipment at a time.
- 7. Make sure your equipment is correctly assembled before you use it. Be sure all screws, nuts, and bolts are tightened prior to use.
- 8. Do not operate this or any exercise equipment if it is damaged.
- 9. Wait 2 hours after eating before using the exercise equipment. If you get nauseous, stop exercising right away.
- 10. Always use this equipment on a clear and level surface. Do not use outdoors or near water.
- 11. Keep hands and feet away from any moving parts. Do not insert any object into any openings.
- 12. Keep loose clothes, jewelry, limbs and long hair away from moving parts.
- 13. Children under the age of 13 should not use this fitness equipment.
- 14. Children from 13 to 18 should have adult supervision.


WARNING: It is highly recommend that you have assistance during the assembly of the equipment.

WARNING: Before using this equipment you should consult with your personal physician to see if the product is appropriate for you. Do not use this equipment without your physician's approval. Do not use this equipment if you have any of the following conditions or ailments:

- Extreme obesity
- Glaucoma, retinal detachment or conjunctivitis
- Pregnancy
- Spinal injury, Cerebral Sclerosis, or acutely swollen joints
- Middle ear infection
- High blood pressure, Hypertension, Recent stroke or Transient ischemic attack
- Heart or circulatory disorders for which you are being treated
- Hiatus hernia or Ventral hernia
- Bone weaknesses including Osteoporosis, Unhealed fractures, Modularly pins, or Surgically implanted orthopedic supports
- Use of anti-coagulants including Aspirin in high doses

Do not exceed the maximum rated weight (load)
The maximum weight capacity of this machine is 800lbs/363kgs.

OVERVIEW DRAWING




PARTS LIST


Part#	Description	Q'ty.	
1	Main Frame	1	
2	Front Support Tube	1	
3	Front Stabilizer	1	
4	Rear Stabilizer	1	
5	Rear Support Tube	1	
6	U-Shaped Bracket		
7	7 Backrest Supporter		
8	Seat Bracket	1	
9	Metal Plate	1	
10	Seat U-Shaped Bracket	1	
11	Rod	2	
12	Leg Holder	1	
13	Seat	1	
14	Backrest	1	
15	Foam Roller		
16	Foam Roller End Cap	2	
17	Round End Cap Ø25*1.5	2	
18	Round End Cap Ø50*1.5	2	
19	Rear Stabilizer End Cap Ø60	2	
20	Transport Wheel Ø60	2	
21	Bushing Ø19	2	
22	EVA Pad	1	
23	Square End Cap □38*2.0mm	2	

Part#	Description	Q'ty.
24	Pin Ø8*143mm	1
25	Pin Ø10*139mm	1
26	Round Knob	1
27	Pin Ø12*100mm	1
28	28 Buffer	
29	Carriage Bolt M10*75	4
30	Spring Washer Ø16.5xØ10x3.0	4
31	Curved Washer Ø25xØ10x2.0	4
32	Cap Nut M10	4
33	Hex Bolt M12*110mm	1
34	Flat Washer Ø24xØ12x2.0	10
35	Anti-Loosen Nut M12	5
36	Hex Bolt M8*55mm	4
37	Flat Washer Ø20xØ8.5x2.0	21
38	38 Anti-Loosen Nut M8	
39	Pan Head Hex Bolt M8*50mm	4
40	Pan Head Hex Bolt M8*20mm	1
41	Axle M12	2
42	Hex Bolt M8*35mm	4
43	43 Casing Ø12xØ8.5x4.544 Hex Bolt M8*25mm	
44		
45	Self-Tapping Phillips Screw ST4*20	1
46	Spring WasherΦ20xΦ8.5x2.0	13

HARDWARE & TOOLS PACK




ASSEMBLY



STEP 1

- **1A.** Rest the Bench on its side and completely pull out the **Pin (27)** from the bracket on the **Main Frame (1)**.
- **1B.** Pull the **Front Support Tube (2)** outwards and completely reinsert the **Pin (27)** into the first hole on the bracket of **Main Frame (1)**.

ASSEMBLY




STEP 2

- 2A. Installing the Front Stabilizer: Lift up the Front Support Tube (2), and then align the Front Stabilizer (3) holes with the holes on the front curve of the Front Support Tube (2). The square holes of the Front Stabilizer (3) should point towards the floor. Insert two Carriage Bolts (29) from the bottom, through the Front Stabilizer (3) and Front Support Tube (2) until the bolts reach through. On the protruding end of the Carriage Bolts (29), secure two Curved Washers (31), two Spring Washers (30), and two Cap Nuts (32). Tighten the Cap Nuts (32) with the Open Wrench provided.
- 2B. Installing the Rear Stabilizer: Lift up the rear of the Main Frame (1), and then align the Rear Stabilizer (4) holes with the holes on the rear curve of the Main Frame (1). The square holes of The Rear Stabilizer (4) should point towards the floor with the Customer Service Stickers facing upward. Insert two Carriage Bolts (29) from the bottom, through the Rear Stabilizer (4) and the rear curve of the Main Frame (1) until the bolts reach through. On the protruding end of the Carriage Bolts (29), secure two Curved Washers (31), two Spring Washers (30), and two Cap Nuts (32). Tighten the Cap Nuts (32) with the two Open Wrench provided.

Hardware:

4 PCS




9

4 PCS

4 PCS


4 PCS



3A. Installing the Leg Holder: Insert the threaded end of the Round Knob (26) into the Main


Frame (1) . Align the Leg Holder (12) insert it into Main Frame (1), pull the Round Knob (26) at the same time. Let go of the Round Knob (26) and continue inserting the Leg Holder (12) until the Round Knob (26) POPS. Tighten the Round Knob (26) in a CLOCKWISE manner to secure the Leg Holder (12) in place.

ASSEMBLY




4A. Installing the Rod & Foam Roller: Insert the Rod (11) onto the top of Leg Holder (12), and insert two Foam Rollers (15) into the Rod (11). Attach both Foam Roller End Caps (16) on the end of the Rod (11).

ASSEMBLY



STEP 5

5A. Installing the Rod & Foam Roller: Insert the Rod (11) onto the lower of Leg Holder (12), and insert two Foam Rollers (15) into the Rod (11). Attach both Round End Caps (17) onto the Rod (11).




Seat Angle Adjustment

Pull the Pin (25) out from the Seat Bracket (8) and adjust the Seat (13) into one of the following positions:

- a. Position A gives a flat and level seat for working out. See Fig A.
- b. Position B gives an inclined seat for working out. See Fig. B
- c. Position C gives an inclined seat for working out. See Fig. C

Completely re-insert the Pin (25) into the hole of the Seat Bracket (8) to secure the seat at desired position.




Adjusting the Seat Forward and Back

Pull the Pin (24) out from the Seat Bracket (8) and adjust the Seat (13) into one of the following positions:

- d. Position D gives a flat and level seat for working out. See Fig D.
- e. Position E gives an inclined seat for working out. See Fig. E.
- f. Position F gives an inclined seat for working out. See Fig. F.


Completely re-insert the Pin (24) into the hole of the Seat Bracket (8) to secure the seat at desired position.



Adjusting the Backrest


Push the **Backrest (14)** upwards to lift the **Rear Support Tube (5)** off of the tabs that run along the rear shaft of the **Main Frame (1)**. Then gently lower the **Backrest (14)** while guiding the **Rear Support Tube (5)** back into the new tab height so that your backrest angle is adjusted. There are six different adjustments:


- 1. $A = 85^{\circ}$
- 2. **B** = 60°
- 3. $C = 45^{\circ}$
- 4. $D = 30^{\circ}$
- 5. **E = 20**°
- 6. $F = 0^{\circ}$
- 7. $G = -15^{\circ}$



Reversible Backrest

The preinstalled **Backrest (14)** is set at 9" wide at the top and 10" wide at the other end. To reverse for a wider backrest, loosen four **Pan Head Hex Bolts (39)**, four **Flat Washers (37)**, four **Spring Washers (46)**, on the back of the **Backrest Supporter (7)**. Loosen **Pan Head Hex Bolt (40)** but do not remove.






Rotate the **Backrest (14)** CLOCKWISE.


After reversal, tighten four Pan Head Hex Bolts (39), four Flat Washers (37), four Spring Washers (46), on the back of the Backrest Supporter (7) and re-tighten Pan Head Hex Bolt (40).

TRANSPORTATION



Transporting when the bench is set up:

Lift up the **Front Stabilizer (3)** until the **Transport Wheels (20)** make contact with the ground, then move the bench to your desired location.



Transporting In Storage Mode:

Lift up the bench by holding the **Seat (13)** until the wheels on the **Transport Wheels (20)** make contact with the ground, then move the bench to your desired location.

WARRANTY

MANUFACTURER'S LIMITED WARRANTY

Paradigm Health & Wellness warrants to the original purchaser that this product is free from defects in material and workmanship when used for the purpose intended, under the conditions that it has been installed and operated in accordance with Paradigm's Owner's Manual. Paradigm's obligation under this warranty applies to the following:

COMPONENT	LENGTH OF WARRANTY
Structural Frame	1 year For Home Use Only
All Other Components	90 days For Home Use Only (computer display, electronics, upholstery, foam,
	ball bearings, pulleys, belts, cables, wires, shocks, covers, tension, internal mechanism,
	wheels, pedals, knobs, accessories and hardware)

Exclusions from Warranty Coverage:

Paradigm does not warrant against and is not responsible for, and no implied warranty shall be deemed to cover, any product failure, product malfunction, or damages attributable to:

- 1. Improper installation and/or failure to abide by Paradigm's installation guidelines;
- 2. Use of this product beyond normal home use, or in an application for which it was not designed;
- 3. Cosmetic items such as scratches, dents or discolorations;
- 4. Damage caused by normal wear and tear, vandalism, and accidental or by animals;
- 5. Any act of Nature (such as fire, flooding, snow, ice, hurricane, earthquake, lightning or other natural disaster), environmental condition (such as air pollution, mold, mildew, etc.), or staining from foreign substances (such as dirt, grease, oil, etc.);
- 6. Normal weathering due to exposure to sunlight, weather and atmosphere which can cause colored surfaces to, among other things, flake, chalk, or accumulate dirt or stains; or
- 7. Improper operation, alteration, handling, storage, abuse or neglect of the products.

Paradigm, using its sole discretion, will either repair or replace free of charge any part(s) proven to be defective under normal home use. Any repair or replacement shall provide no new warranty coverage, but shall retain only the remaining portion of the original product's warranty. All exchanged parts and Products replaced under this limited warranty will become the property of Paradigm Health and Wellness. This warranty is offered only to the original purchaser and is not transferable. Proof of original purchase is required.

Ordering Replacement Parts

Replacement parts can be ordered by emailing our customer service department:

Service@paradigmhw.com

Open Monday Thru Friday, 8:00 AM - 5:00 PM (PST).

When ordering replacement parts please have the following information ready:

- 1. Owner's Manual
- 2. Model Number
- 3. Description of Parts
- 4. Part Number
- 5. Date of Purchase

PARTS REQUEST

Paradigm Health & Wellness, Inc.

EMAIL THIS FORM WITH YOUR RECEIPT OF PURCHASE TO Service@paradigmhw.com

NΑ	ME:				
СІТ	Y:	STATE:	ZIP:		
TE	LEPHONE: (Day)_				
SE					
		E:			
	PART#	DESCRIPTION		QTY	

[&]quot;YOUR ORDER WILL BE PROCESSED WITHIN 3 BUSINESS DAYS"

^{*} This form can also be faxed in Fax #: 626-810-2166