

## 25 mm Standard Wirefree Tubular Motor RTML25



Li-ion battery powered motorized shades are a perfect retro fit for existing homes or small commercial projects. Li-ion powered motors require no electrical wiring, no external battery pack and no complicated installation.

**The standard 25 mm motor allows a maximum shade size of 84" x 84" and has a 21 ½" minimum shade width / roller tube length.**



### 2-Way RF Communication

Integrated radio frequency control allows for easy programming of individual, group or ALL control across window treatments.



### Leveling Control

This feature allows for precise positioning of multiple window treatments, ensuring perfect alignment.



### Preferred Upper / Lower Limit Settings

Electronic "autoset" limits accurately program preferred upper and lower limit settings.



### Favorite Position

Allows a most used or favorite position to be set between upper and lower limit settings.




### Adjustable Speed

Three operational speed settings available, allowing you to customize the open / close speed of your shade.



### Optimal Solar Recharge Option

Pairs with optional solar panel battery charger for autonomous recharging of the built-in li-ion battery.



### IOT Integration

Pairs with several voice control systems using the R-TEC Hub and Automation<sup>®</sup> App, including Apple HomeKit, Amazon Alexa, Google Assistant, IFTTT and SmartThings.




### Battery Powered

Rechargeable built-in Li-ion battery that operates up to 500 up and down cycles per charge (based on recommended shade size).


# SPECIFICATIONS

Voltage	12 V DC	Limit Switch Type	Electronic
Torque	1.1 Nm	Amps	0.83 A
Max. Run Time	10 min.	Battery Size / Type	1400 mAh
Speed	40 RPM (Adj. to 30 or 20)	Temperature Working Range	32° F - 140° F (0° C - 60° C)
Radio Frequency	433.92 MHz	Insulation Class	III
RF Modulation	FSK	Sound Level	~46 DB
IP Rating	IP44		

# DIMENSIONS



# APPLICATIONS



# USE WITH

## Compatible Power Options

Item #	Description
RTMLBC	Battery Charger 12', .4Amp, 12V
RTMLCXT48	Charger Cable Extender 48", 12V
RTMLCXT96	Charger Cable Extender 96", 12V
RTMSOLAR2	Solar Panel Battery Charger

## Compatible Brackets & Bracket Covers

Item #	Description
RSB10	Bracket: 1 5/8" Projection, 2 1/4" Width
RSB20	Bracket: 2 1/8" Projection, 2 1/4" Width
RSBC10/	Bracket Cover for RSB10 (SN, W or K)
RSBC20/	Bracket Cover for RSB20 (SN, W or K)
RSNB10	Bracket: 1 5/8" Projection, 1 1/2" Width
RSNB20	Bracket: 2 1/8" Projection, 1 1/2" Width
RSNB30	Bracket: 2 7/8" Projection, 1 1/2" Width

## Compatible Drive Set Kits & Motor End Cover Kits

Item #	Description
RTMDRK25114	1 1/4" Drive Set Kit (includes motor adapter plate, crown & drive set and end pin)
RTMDRK25112	1 1/2" Drive Set Kit (includes motor adapter plate, crown & drive set and end pin)
RTMMC25/	25 mm Motor End Cover Kit (W or K)

## Compatible R-TEC Smart Controls

Item #	Description
RTMHR1C	Handheld Remote with Wall Mount, 1 Channel, Range: 65'
RTMHR5C	Handheld Remote with Wall Mount, 5 Channel, Range: 65'
RTMHR15C	Handheld Remote with Wall Mount, 15 Channel, Range: 65'
RTMWSR5C	Surface Wall Mount Switch, 5 Channel, Range: 65'
RTMWSR15C	Wall Box Mount Switch, 15 Channel, Range: 65'
RTMHUB2	R-TEC Hub, includes USB Power Cord, Power Plug & Ethernet Cable, Range: 60'
RTMISS	Interior Sun Sensor, Range: 65'
RTMUSR	ARC USB Signal Repeater, Extends the wireless range of the R-TEC Hub and Remotes up to 60'. Max. 2 per system.
RTMLWCW	Wall Charger for USB Signal Repeater

## Compatible Aluminum Rollers

Item #	Description
RC58/4	1 1/4" (4', 6', 8', 12' or 16' lengths)
RC60/4	1 1/2" (4', 6', 8', 12' or 16' lengths)