

FABRICATION

Rowley project list: Non-Slouching Couch Pillow

This is a great pillow to use on leather couches or chairs as it will not slide or slouch down once it's placed on the furniture – the secret is the flat bottom. It's easy to make once you understand the math and using a down insert adds to the overall comfort of use.



MATERIALS & SUPPLIES

Rowley Products	SKU
Fusible Stabilizer	<u>FB11</u>
5/32" Polyester Welt Cord	<u>WCP0/</u>
4.5 Nylon Zipper	<u>ENR25/</u>
Zipper Slide	ENP2
10/90 18"x18" Down Insert	FD18/10

NON-SLOUCHING COUCH PILLOW: STEP-BY-STEP INSTRUCTIONS

This project covers the steps to fabricate the bottom boxed pillow with welt cord and a zipper. Our pillow finished at 17"W x 11"H – just perfect for the side of a couch!

The illustrations vary between two fabrics (floral and geometric), although the pillow should be made using only one – this is entirely my fault. I did not take photos from start to finish with one fabric only.

Cutting and Prepping the Fabric:

Cut the pillow front and back into a trapezoid shape with slightly rounded top corners.

- A. The top will measure 18"W. Round off the corners after you cut the trapezoid.
- B. The bottom will measure 23"W.
- C. The cut height is 12".

2

Cut two strips for the zipper at 22" x 5" each.

A. Your zipper will be longer than what you need for the pillow. It will be trimmed during fabrication to the correct length.



Fold the strips in half lengthwise and iron to set a crease.

Apply a layer of fusible stabilizer to the back of the fabric on both top and back pieces.

Cut and make enough welt cord to go up one side, along the top and down the other side only.



Making the Pillow:



Sew welt cord to the pillow front, sewing up one side, across the top and down the other side.

2

With right sides together, and matching tops, corners and bottoms, sew the front to the back, on the top and two sides only.





Cut a length of zipper chain a few inches longer than your strips. Load the zipper pull on one end.

Using the two prepared zipper strips, sew in a flap zipper.






G

6

Align the welt cord seam to one end of the zipper strip, right sides together. Pin.

Continue to pin the zipper strip to the pillow along the long edges, but do not do the other end of the zipper yet. **A.** You will need to make a relief cut in the pillow fabric to turn the corner with the zipper strip.









FABRICATION



Sew the pinned sides.

At the open zipper end, make the same two relief cuts in the pillow fabric so it will lay flat against the zipper strip.



8

Mark for needed length.



j.

Move the zipper pull up the zipper strip and cut the strip to the needed length.



Pin zipper end to pillow and finish sewing.











(13

Stuff and close zipper.

A. Pushing the bottom of the insert into itself to create a flat bottom will help shape the pillow.

Turn right sides out. Your goal is to have the zipper centered on the decorative welt cord.









©2013 Rowley Company LLC | All rights reserved.